

# DataCell




[www.DataCell.co](http://www.DataCell.co)

# W

Flow Measurement  
Pressure Measurement  
Location Identification

- Inputs:
  - 1 flow counter
  - 1 pressure channel
  - GPS enabled
- Measure:
  - flow
  - pressure
- Log:
  - flow
  - pressure
- Alarm:
  - pressure high
  - pressure low
- Location:
  - GPS enabled
- Next G
  - data returned as scheduled
  - instant alarm notification
  - send to system
  - send to phone
- Rugged/Waterproof /Independent
  - IP68
  - Battery powered
- Integrate to:
  - SCADA
  - BMS
  - SQL
  - Monitoring Systems
  - Web Hosted Systems



**AEGIS**



## Product Overview

The DataCell advanced data logger has been designed to provide automated remote monitoring and analysis of systems and environments critical to your needs.

The DataCell has been designed to be maintenance free, specifically for the harsh, remote environments where it is usually deployed.

Being battery powered and completely self contained the DataCell can monitor powered or unpowered networks independent of the mains supply, enabling critical system measurement, monitoring, and alarming.

The data from the DataCell is returned to you via the Next G/3G/GSM/GPRS network and can be automatically integrated into your business systems for analysis. KPI reports, trend analysis and alarming become a breeze and allow you to concentrate on business improvement rather than analysis.

Data can be returned directly to your system or displayed on the DataScope web platform.

Being absolutely independent of any other support systems, the DataCell is truly self sufficient.

Installation simply involves mounting the unit and sensor - no field calibration or configuration is required. The exceptional battery life will result in a low 'whole of life' cost of ownership.

## Specifications - CZ21075

### Inputs

Pressure Channel:	± 100 mV 3.3V supply
Flow Channel:	100 Hz max
GPS:	Integrated

### Logging

Memory:	16,000 records
Alarms:	High/Low pressure

### Communications

Serial:	USB interface
Wireless:	Next G/3G/GSM/GPRS
Protocols:	TCP, FTP, Email, SMS
Delivery:	Data programmable from 1 hour Alarms - immediate

### Clock

Real time with SNTP time update

### Battery

Type:	3.6V Primary LiSOCl <sub>2</sub>
Life:	Typically 5 years, configuration dependant

### Physical

Dimensions:	68mmØ x 170mm
Weight:	415 grams
Environmental :	IP68
Operating Temperature:	0°C to +50°C
Storage Temperature:	-20°C to +70°C

### Applicable Standards

AS 60529-2004: IP68	IEC 60529 Ed 2.1: IP68
AS/NZS 60950.1:2011	EN 60950-1:2006/A11:2009
AS/NZS CISPR 22:2009	
CE	
RMC	



### Australia Aegis

Toll Free: 1300 723 447  
sales@aegis.net.au  
www.aegis.net.au

### United Kingdom Aegis Instruments

Toll Free: 0800 6123447  
sales@aegisinstruments.co.uk  
www.aegisinstruments.co.uk

### New Zealand Aegis Instruments

Toll Free: 0800 023447  
sales@aegis.net.nz  
www.aegis.net.nz